

**MAINTENANCE INSTRUCTION – POLYFLOR TECHNICAL VINYL FLOORING**  
Homogeneous Vinyl Flooring with PUR surface treatment

**POLYFLOR  
PRIMUS 2000 PUR**

**POLYFLOR  
PRESTIGE PUR**

**POLYFLOR  
TREND PUR**

**POLYFLOR  
MYSTIQUE PUR**

**POLYFLOR  
PEARLAZZO PUR**

**1. GENERAL INFORMATION**

Well planned and regular maintenance, tailored to traffic conditions and frequencies, will help keep the floorcovering in pristine condition. Without regular maintenance, standards of appearance, hygiene and cleanliness, as well as the life expectancy of the floorcovering, will be compromised.

**2. PREVENTATIVE MEASURES**

In the initial stages of construction planning, attention should be paid to minimising the amount of dirt and water that can enter the building. To facilitate this we strongly recommend the installation of passive dirt barrier systems in all entrance areas e.g. scraper and moisture mats. The mats should be positioned to ensure that access cannot be gained without walking on them, ideally they should be at least six paces wide.

**3. INITIAL CONSTRUCTION CLEAN**

After the flooring has been installed, all dirt and construction debris should be completely removed and the floor swept clean. Use a PU or a neutral detergent for floorcoverings with a PUR factory applied surface treatment.

**4. APPLICATION OF A FLOORDRESSING**

It is not necessary to apply such a protection to objectflor floorcoverings with a PUR surface treatment as this treatment will provide permanent protection.

**5. ROUTINE MAINTENANCE**

**Daily**

Mop sweep or vacuum the floor to remove dust and loose dirt. Remove any soiling by using a neutral or a PU cleanser then damp mop with a cloth. If required, dry buff with a high-speed rotary machine and a white pad.

**Weekly**

Remove all light soiling and traces of scuffing using a 1000 rpm rotary machine fitted with a white or a red pad. For heavier scuffing spray clean using a floor maintainer and 1000 rpm plus rotary machine.

**6. PERIODIC MAINTENANCE**

If the floor has dirt build-up it may be necessary to clean the floorcovering with an alkaline detergent according to the manufacturers instructions. For this periodical maintenance burnish the surface treatment with a suitable rotary machine or by additionally using a spray cleaning product. This will improve the PUR surface protection and it will improve the appearance of the floorcovering. For both cases use a soft pad (white, maximum red).

**7. REMOVAL OF A FLOORDRESSING**

This is not necessary for floorcoverings with a factory applied PUR surface treatment as the PUR treatment provides a permanent protection.

**8. GENERAL INFORMATION**

**Always remove all chemical spillage immediately in order to avoid intensive damage of the original appearance.**

**Always follow the Health and Safety guidance issued by the cleaning product and machinery manufacturers. Always use the dilution rates and timings as recommended by the cleaning product manufacturers.**

For further guidance contact objectflor Customer Technical Support or visit our homepage: [www.objectflor.de](http://www.objectflor.de)

**MAINTENANCE INSTRUCTION – POLYFLOR TECHNICAL VINYL FLOORING**  
Homogeneous Vinyl Flooring with PU surface treatment

**POLYFLOR  
ULTRA XL PU**

**POLYFLOR  
EXTRA PU**

**1. GENERAL INFORMATION**

Well planned and regular maintenance, tailored to traffic conditions and frequencies, will help keep the floorcovering in pristine condition. Without regular maintenance, standards of appearance, hygiene and cleanliness, as well as the life expectancy of the floorcovering, will be compromised.

**2. PREVENTATIVE MEASURES**

In the initial stages of construction planning, attention should be paid to minimising the amount of dirt and water that can enter the building. To facilitate this we strongly recommend the installation of passive dirt barrier systems in all entrance areas e.g. scraper and moisture mats. The mats should be positioned to ensure that access cannot be gained without walking on them, ideally they should be at least six paces wide.

**3. INITIAL CONSTRUCTION CLEAN**

After the flooring has been installed, all dirt and construction debris should be completely removed and the floor swept clean.

For floorcoverings with a PU surface treatment use a PU or a neutral detergent.

**4. APPLICATION OF A FLOORDRESSING**

It is not necessary to apply such a protection to objectflor floorcoverings with a PU surface treatment.

If required after the installation dry buff the flooring with a mono-pad rotary machine (400rpm) fitted with a white pad.

In such areas as hairdressing salons and any location where chemical substances are regularly being used it is recommended to add additional protection by application of a high solid metalised polish.

**5. ROUTINE MAINTENANCE**

**Damp mop**

Damp mop the floor using a floor maintainer, then thoroughly wring out the mop and repeat to remove any residue.

Use a neutral or a PU detergent for floorcoverings with a factory applied PU treatment.

**Spray Cleaning / Burnishing**

Burnish the floor by using a rotary machine (minimum 400 rpm) using a polishing brush and clean the floor by additionally using a spray cleaning product. This will add further protection and it will improve the appearance of the floorcovering.

In both in cases use a soft pad (white, max. red.)

**6. PERIODIC MAINTENANCE**

If the floor has dirt build-up it may be necessary to clean the floorcovering with an alkaline detergent according to the manufacturers' instructions.

**7. REMOVAL OF A FLOORDRESSING**

From time to time it will be necessary to strip back the polish layers, e.g. when routine maintenance does no longer bring about a satisfactory result. The interval is very much dependant on traffic conditions and maintenance methods. All soiling and any unsightly build up of polish should be removed by initially applying an emulsion polish stripper and the slurry should be removed completely. Then proceed as described in 4.

Floorcoverings with a factory applied surface treatment may also require the application of a floordressing of the polymeric dispersion type or the PU sealing type. This may be the case when the appearance of the floorcovering has deteriorated.

**8. GENERAL INFORMATION**

**Always remove all chemical spillage immediately in order to avoid intensive damage of the original appearance.**

**Always follow the Health and Safety guidance issued by the cleaning product and machinery manufacturers. Always use the dilution rates and timings as recommended by the cleaning product manufacturers.**

For further guidance contact objectflor Customer Technical Support or visit our homepage: [www.objectflor.de](http://www.objectflor.de)

**MAINTENANCE INSTRUCTION – POLYFLOR TECHNICAL VINYL FLOORING**  
Heterogeneous Vinyl Flooring with PUR surface treatment

**POLYFLOR  
LIGNO FX PUR**

**POLYFLOR  
MINERAL FX PUR**

**1. GENERAL INFORMATION**

Well planned and regular maintenance, tailored to traffic conditions and frequencies, will help keep the floorcovering in pristine condition. Without regular maintenance, standards of appearance, hygiene and cleanliness, as well as the life expectancy of the floorcovering, will be compromised.

**2. PREVENTATIVE MEASURES**

In the initial stages of construction planning, attention should be paid to minimising the amount of dirt and water that can enter the building. To facilitate this we strongly recommend the installation of passive dirt barrier systems in all entrance areas e.g. scraper and moisture mats. The mats should be positioned to ensure that access cannot be gained without walking on them, ideally they should be at least six paces wide.

**3. INITIAL CONSTRUCTION CLEAN**

After the flooring has been installed, all dirt and construction debris should be completely removed and the floor swept clean. Use a PU or a neutral detergent for floorcoverings with a PUR factory applied surface treatment.

**4. APPLICATION OF A FLOORDRESSING**

It is not necessary to apply such a protection to objectflor floorcoverings with a PUR surface treatment as this treatment will provide permanent protection.

**5. ROUTINE MAINTENANCE**

**Daily**

Mop sweep or vacuum the floor to remove dust and loose dirt. Remove any soiling by using a neutral or a PU cleanser then damp mop with a cloth. If required, dry buff with a high-speed rotary machine and a white pad.

**Weekly**

Remove all light soiling and traces of scuffing using a 1000 rpm rotary machine fitted with a white or a red pad. For heavier scuffing spray clean using a floor maintainer and 1000 rpm plus rotary machine.

**6. PERIODIC MAINTENANCE**

If the floor has dirt build-up it may be necessary to clean the floorcovering with an alkaline detergent according to the manufacturers instructions. For this periodical maintenance burnish the surface treatment with a suitable rotary machine or by additionally using a spray cleaning product. This will improve the PUR surface protection and it will improve the appearance of the floorcovering. For both cases use a soft pad (white, maximum red).

**7. REMOVAL OF A FLOORDRESSING**

This is not necessary for floorcoverings with a factory applied PUR surface treatment as the PUR treatment provides a permanent protection.

**8. GENERAL INFORMATION**

**Always remove all chemical spillage immediately in order to avoid intensive damage of the original appearance.**

**Always follow the Health and Safety guidance issued by the cleaning product and machinery manufacturers. Always use the dilution rates and timings as recommended by the cleaning product manufacturers.**

For further guidance contact objectflor Customer Technical Support or visit our homepage: [www.objectflor.de](http://www.objectflor.de)

**MAINTENANCE INSTRUCTION – POLYFLOR TECHNICAL VINYL FLOORING**  
Heterogeneous Vinyl Flooring with PUR surface treatment

**POLYFLOR  
ACOUSTIX  
GALLERY FX**

**POLYFLOR  
ACOUSTIX  
FOREST FX**

**1. GENERAL INFORMATION**

Well planned and regular maintenance, tailored to traffic conditions and frequencies, will help keep the floorcovering in pristine condition. Without regular maintenance, standards of appearance, hygiene and cleanliness, as well as the life expectancy of the floorcovering, will be compromised.

**2. PREVENTATIVE MEASURES**

In the initial stages of construction planning, attention should be paid to minimising the amount of dirt and water that can enter the building. To facilitate this we strongly recommend the installation of passive dirt barrier systems in all entrance areas e.g. scraper and moisture mats. The mats should be positioned to ensure that access cannot be gained without walking on them, ideally they should be at least six paces wide.

**3. INITIAL CONSTRUCTION CLEAN**

After the flooring has been installed, all dirt and construction debris should be completely removed and the floor swept clean. Use a PU or a neutral detergent for floorcoverings with a PUR factory applied surface treatment.

**4. APPLICATION OF A FLOORDRESSING**

It is not necessary to apply such a protection to objectflor floorcoverings with a PUR surface treatment as this treatment will provide permanent protection.

**5. ROUTINE MAINTENANCE**

**Daily**

Mop sweep or vacuum the floor to remove dust and loose dirt. Remove any soiling by using a neutral or a PU cleanser then damp mop with a cloth. If required, dry buff with a high-speed rotary machine and a white pad.

**Weekly**

Remove all light soiling and traces of scuffing using a 1000 rpm rotary machine fitted with a white or a red pad. For heavier scuffing spray clean using a floor maintainer and 1000 rpm plus rotary machine.

**6. PERIODIC MAINTENANCE**

If the floor has dirt build-up it may be necessary to clean the floorcovering with an alkaline detergent according to the manufacturers instructions. For this periodical maintenance burnish the surface treatment with a suitable rotary machine or by additionally using a spray cleaning product. This will improve the PUR surface protection and it will improve the appearance of the floorcovering. For both cases use a soft pad (white, maximum red).

**7. REMOVAL OF A FLOORDRESSING**

This is not necessary for floorcoverings with a factory applied PUR surface treatment as the PUR treatment provides a permanent protection.

**8. GENERAL INFORMATION**

**Always remove all chemical spillage immediately in order to avoid intensive damage of the original appearance.**

**Always follow the Health and Safety guidance issued by the cleaning product and machinery manufacturers. Always use the dilution rates and timings as recommended by the cleaning product manufacturers.**

For further guidance contact objectflor Customer Technical Support or visit our homepage: [www.objectflor.de](http://www.objectflor.de)

**MAINTENANCE INSTRUCTION – POLYFLOR TECHNICAL VINYL FLOORING**  
Safety Vinyl Flooring with PUR surface treatment

**POLYSAFE™  
MOSAIC PUR**

**POLYSAFE™  
CORONA PUR**

**POLYSAFE™  
STANDARD PUR**

**1. GENERAL INFORMATION**

Well planned and regular maintenance, tailored to traffic conditions and frequencies, will help keep the floorcovering in pristine condition. Without regular maintenance, standards of appearance, hygiene and cleanliness, as well as the life expectancy of the floorcovering, will be compromised.

**2. PREVENTATIVE MEASURES**

In the initial stages of construction planning, attention should be paid to minimising the amount of dirt and water that can enter the building. To facilitate this we strongly recommend the installation of passive dirt barrier systems in all entrance areas e.g. scraper and moisture mats. The mats should be positioned to ensure that access cannot be gained without walking on them, ideally they should be at least six paces wide.

**3. INITIAL CONSTRUCTION CLEAN**

After the flooring has been installed, all dirt and construction debris should be completely removed and the floor swept clean. For floorcoverings with a PUR surface treatment a PU- or intensive cleaner has to be used and diluted following the manufacturer's instructions. The slurry should be removed completely and the area rinsed thoroughly with clean water to restore a neutral pH value.

**4. APPLICATION OF A FLOORDRESSING**

It is not necessary to apply such a protection to objectflor floorcoverings with a PUR surface treatment.

**5. ROUTINE MAINTENANCE**

**By hand:**

Good cleaning results are achieved by using a two-stage cleaning process (double mop system with a mobile double bucket unit) or with a special single-stage cleaning process using suitable care products.

**By machine:**

Cleaning by machine is suitable for large, clear areas. In this case, special machine cleaners are used in accordance with the cleaning product manufacturer's recommendations.

**Spray Cleaning/Burnishing**

Burnish the floor by using a rotary machine using a polishing brush and clean the floor by additionally using a spray cleaning product. This will add further protection and it will improve the appearance of the floorcovering.

**6. PERIODIC MAINTENANCE**

If the floor has dirt build-up it may be necessary to clean the floorcovering with an alkaline detergent according to the manufacturers' instructions.

**7. REMOVAL OF A FLOORDRESSING**

From time to time it will be necessary to strip back the polish layers, e.g. when routine maintenance does no longer bring about a satisfactory result. The interval is very much dependant on traffic conditions and maintenance methods. All soiling and any unsightly build up of polish should be removed by initially applying an emulsion polish stripper and the slurry should be removed completely.

**8. GENERAL INFORMATION**

**Always remove all chemical spillage immediately in order to avoid intensive damage of the original appearance.**

**When choosing cleaning- and care products ensure that they complement each other and follow the manufacturer's instructions. The anti-slip properties of the security flooring must not be compromised.**

For further guidance contact objectflor Customer Technical Support or visit our homepage: [www.objectflor.de](http://www.objectflor.de)

**MAINTENANCE INSTRUCTION – POLYFLOR TECHNICAL VINYL FLOORING**  
Safety Vinyl Flooring without surface treatment

**POLYSAFE™  
HYDRO EVOLVE**

**POLYSAFE™  
ULTIMA**

**POLYSAFE™  
ECOMAX**

**1. GENERAL INFORMATION**

Well planned and regular maintenance, tailored to traffic conditions and frequencies, will help keep the floorcovering in pristine condition. Without regular maintenance, standards of appearance, hygiene and cleanliness, as well as the life expectancy of the floorcovering, will be compromised.

**2. PREVENTATIVE MEASURES**

In the initial stages of construction planning, attention should be paid to minimising the amount of dirt and water that can enter the building. To facilitate this we strongly recommend the installation of passive dirt barrier systems in all entrance areas e.g. scraper and moisture mats.

The mats should be positioned to ensure that access cannot be gained without walking on them, ideally they should be at least six paces wide.

**3. INITIAL CONSTRUCTION CLEAN**

After the flooring has been installed, all dirt and construction debris should be completely removed and the floor swept clean.

In the case of POLYSAFE™ safety floor coverings, a basic cleaning product, diluted as recommended by the cleaning product manufacturer, must be used with a single disc rotary machine with cleaning brush.

The slurry should be removed completely and the area rinsed thoroughly with clean water to restore a neutral pH value.

**4. APPLICATION OF A FLOORDRESSING**

POLYSAFE™ safety floor coverings with no surface treatment must be treated with a suitable care product. Once the protective film has dried, it can be polished using a soft brush/polishing brush.

**5. ROUTINE MAINTENANCE**

**By hand:**

Good cleaning results are achieved by using a two-stage cleaning process (double mop system with a mobile double bucket unit) or with a special single-stage cleaning process using suitable care products.

**By machine:**

Cleaning by machine is suitable for large, clear areas. In this case, special machine cleaners are used in accordance with the cleaning product manufacturer's recommendations.

**Spray Cleaning / Burnishing**

Burnish the floor by using a rotary machine using a polishing brush and clean the floor by additionally using a spray cleaning product. This will add further protection and it will improve the appearance of the floorcovering.

**6. PERIODIC MAINTENANCE**

If the floor has dirt build-up it may be necessary to clean the floorcovering with an alkaline detergent according to the manufacturers' instructions.

**7. REMOVAL OF A FLOORDRESSING**

From time to time it will be necessary to strip back the polish layers, e.g. when routine maintenance does no longer bring about a satisfactory result. The interval is very much dependant on traffic conditions and maintenance methods.

This completely removes all dirt and cleaning product residues using a basic cleaning product and a single disc rotary machine with cleaning brush and the dirty water is completely removed.

**8. GENERAL INFORMATION**

**Always remove all chemical spillage immediately in order to avoid intensive damage of the original appearance.**

**When choosing cleaning- and care products ensure that they complement each other and follow the manufacturer's instructions. The anti-slip properties of the security flooring must not be compromised.**

For further guidance contact objectflor Customer Technical Support or visit our homepage:  
[www.objectflor.de](http://www.objectflor.de)