

Resilient flooring with quick, adhesive-free installation on a wide range of existing subfloors up to 97% RH** – less preparation, quick usability.

Characteristics	Standards	Unit	POLYFLOR GEOTONE QUICKLAY PUR
Type of floor covering	EN ISO 10582		heterogeneous, PVC
Surface treatment			PUR
Description			 non-directional, tonal
Total weight	EN ISO 23997	g/m ²	2700
Use Area	EN ISO 10874		 23  34  42
Gauge	EN ISO 24346	mm	 2,2
Wear layer thickness	EN ISO 24340	mm	1,0
Packaging roll size	EN ISO 24341	m / m ²	 2 m x 20 m / 40 m ²
Dimensional stability	EN ISO 23999	%	≤ 0,4
Residual indentation	EN ISO 24343-1	mm	≤ 0,10
Light Fastness	EN ISO 105-B02	level	≥ 6
Behaviour to fire	EN 13501-1		B _{f1} - s1
Slip resistance	EN 13893 DIN EN 16165 Ann B		DS R10
Impact sound reduction	EN ISO 10140-3	dB	6
Electrostatic properties when walked on	EN 1815	kV	≤ 2,0 antistatic
Bacterial Resistance	ISO 846 Part C		does not favour growth
Resistance to chemicals	EN ISO 26987		*
Binder Content	EN ISO 10582		type I
Castor chair	ISO 4918		yes, type W, EN 12529
Furniture leg	EN ISO 16581		pass
Flexibility	EN ISO 24344		(Method A) Pass 20mm Ø
Underfloor heating	EN 1264-2		suitable, max. 27 °C
VOC emissions	Indoor Air Comfort® GOLD FloorScore® Finnish M1 Classification		Eurofins certified product certified pass
	EN 14041		   



100%
RECYCLABLE



All POLYFLOR commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

* Resistant depending on concentration and time of exposure, in case of increased impact of oils, grease, acids, alkalis and other aggressive chemicals – please contact us.

** If the residual moisture content is very high, the instructions in our installation guide must be observed.

Subject to change due to further technical development.