

EXPONA LIVING

Heterogeneous vinyl floor covering, which is produced using phthalate-free and bio-based plasticisers, available as tiles and planks based on a phototechnical reproduction with a transparent wear layer and a factory applied polyurethane surface treatment suitable for use in heavy duty living areas.

Characteristics	Standards	Unit	EXPONA LIVING
Type of floor covering	EN ISO 10582		heterogeneous, PVC
Surface treatment			PUR
Total weight	EN ISO 23997	g/m ²	3600
Use Area	EN ISO 10874		 23  31
Gauge	EN ISO 24346	mm	2,0
Wear layer thickness	EN ISO 24340	mm	0,3
Packaging tile size	EN ISO 24342	mm	18 @ 304,8 x 609,6 = 3,34 m ²
Packaging plank size	EN ISO 24342	mm	24 @ 152,4 x 914,4 = 3,34 m ² 18 @ 152,4 x 1219,2 = 3,34 m ² 15 @ 184,2 x 1219,2 = 3,37 m ²
Dimensional stability	EN ISO 23999	%	≤ 0,1 **
Residual indentation	EN ISO 24343-1	mm	≤ 0,05 **
Light Fastness	EN ISO 105-B02	level	≥ 6
Reaction to Fire	EN 13501-1		B _{fl} - s1
Slip resistance	EN 13893 DIN EN 16165 Ann. B		DS R10
Impact sound reduction	EN ISO 10140-3	dB	3
Thermal conductivity	EN 12524	W/(mK)	0,25
Assessment of static electrical propensity	EN 1815	kV	≤ 2, antistatic
Resistance to chemicals	EN ISO 26987		*
Binder content	EN ISO 10582		type I
Castor chair	ISO 4918		yes, type W, EN 12529
Underfloor heating	EN 1264-2		suitable, max. 27 °C
VOC emissions	Indoor Air Comfort® GOLD FloorScore® Finnish M1 Classification AgBB VOC test		Eurofins certified product certified pass very low emissions
Environmental product declaration	EN 15804		DGNB Navigator / www.dgnb-navigator.de
Responsible Sourcing	SA 8000		Approved Factory
CE	EN 14041		   



* Resistant depending on concentration and time of exposure, in case of increased impact of oils, grease, acids, alkalis and other aggressive chemicals – please contact us.

** Averaged test value from current production

Subject to change due to further technical development.